EVOLUTION 500 TURBO DIESEL 15W-40

Technical Data Sheet

Multigrade oil developed by ELF, particularly intended to Diesel engines of light vehicles.

1 Applications

All Diesel engines

- Recommended for the Diesel engines in cars and light vans.

All types of course

- Adapted to all types of course (in town, on highways and motorways) and during all times of year.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

2 Performances

International specifications

API SL/CF

OEM approvals

VOLKSWAGEN	VW 501.01 / 505.00
MERCEDES BENZ	MB-Approval 229.1

3 Customer Benefits

Engine cleanliness

- Very good capacity to maintain the soots generated by the gas combustion in suspension. The engines is thus cleaner and its performances are preserved.

Lengthens engine life

- Anti-wear and detergent properties, enabling the engine protection.

4 Characteristics

	METHOD	UNITS	SAE GRADE 15W-40
Density at 15°C	ASTM D1298	kg/m³	885
Viscosity at 100°C	ASTM 445	mm²/s	14,3
Viscosity index	ASTM D2270	-	136
Pour point	ASTM D97	°C	-30
Flash point	ASTM D92	°C	234
B.N.	ASTM D2896	mgKOH/g	9

The typical characteristics mentioned represent mean values

TotalEnergies Lubrifiants
562, avenue du Parc de l'île
92029 Nanterre cedex
FRANCE

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk.
A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.