

ELF EVOLUTION FULL-TECH PCX 0W-30 is a very high performance lubricant using ELF Advanced Synthetic Technology intended for lubricating European Gasoline and Diesel car engines requiring 0W-30 SAE grade.

Technical Data Sheet

International Specifications

ACEA C2
API SN PLUS

Manufacturers Approvals

Approved :
PSA B71 2312, PSA B71 2302

Meets the requirement of :
FIAT 9.55535-GS1, FIAT 9.55535-DS1
JAGUAR LAND ROVER STJLR.03.5007

Suitable for :
TOYOTA

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

ELF EVOLUTION FULL-TECH PCX 0W-30 was formulated to ensure compatibility with post-treatment systems. It is suitable for recent engines of Stellantis/PSA, and particularly the ones equipped with e-HDI using Stop & Start technologies, and hybrid engines which require new-generation engine oils.

2 - Customer Benefits

Ensures compliance with all performance levels required by PEUGEOT, CITROEN and DS.

Optimizes post-treatment systems allowing a strong reduction of pollutant emissions, thanks to its low levels of Sulphated Ash, Phosphorus and Sulphur (low SAPS).

Exceptional wear protection for engine longevity.

Even at very low temperatures, it makes cold engine starts easier, thanks to the special additives package.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	843
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	50.1
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.8
Viscosity index	ASTM D2270	-	187
Pour point	ASTM D97	°C	-48
Flash point	ASTM D92	°C	234
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.