



ELF EVOLUTION FULL-TECH PCX FE 0W-20 is an advanced synthetic engine oil, formulated for Stellantis group vehicles maintenance.



Technical
Data Sheet

International Specifications	ACEA C5 API SN PLUS
Manufacturers Approvals	Approved : PSA B71 2010 Opel/Vauxhall OV 040 1547 - A20 Meets the requirements for : FIAT 9.55535-DM1

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

ELF EVOLUTION FULL-TECH PCX FE 0W-20 provides engine with the best possible protection against wear and clogging.

The post-treatment systems, sensitive to the lubricants used and expensive to maintain, are also protected over the long-term thanks to the "Low SAPS" formulation (low content of sulphated ash, phosphorus and sulphur contents). It is also suitable for the most demanding driving conditions (door-to-door, sporty driving, repeated start-ups, city and motorway driving, etc.).

2 - Customer Benefits

Thanks to its low viscosity and Friction modifiers EVOLUTION FULL-TECH PCX FE 0W-20 allows a lower movement resistance and therefore exceptional fuel saving performance over time.

The combination of synthetic oil and high-tech additives ensure the best protection against wear & clogging and increase the vehicle's life duration.

Thanks to its low-saps formulation EVOLUTION FULL-TECH PCX FE 0W-20 extend the DPF service life preventing risk of breakdowns and immobilization.



3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	845,4
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	43,9
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	8,2
Viscosity index	ASTM D2270	-	166
Pour point	ASTM D97	°C	-42
Flash point	ASTM D92	°C	233
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.