



A brand of **TOTAL**

ELF GARDEN 4T 15W-40



Mineral lubricant, suitable for 4 stroke gasoline or Diesel engines used in mechanized farming.

APPLICATIONS

- ELF GARDEN 4T 15W-40 is particularly adapted to **4 stroke gasoline or Diesel engines**, for **gardening and mechanized farming**.

SPECIFICATIONS AND APPROVALS

International specifications

ACEA A3/B3

API SJ/CG-4

PERFORMANCES AND CUSTOMER BENEFITS

- ELF GARDEN 4T 15W-40 has **outstanding thermal stability**, ensuring efficient lubrication of hot engine parts.
- Its **exceptional oil film resistance when hot** guarantees good engines operation and no performance losses.
- ELF GARDEN 4T 15W-40 contains **excellent viscosity stability** in service, providing **smooth cold starts**.
- The **association of detergent, dispersant and anti-wear additives** keeps the engine clean and enables effective control of soot, sludge and piston deposits.
- Its **anti-rust and anti-corrosion properties** protect the engine from moisture damages.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

ELF GARDEN 4T 15W-40*		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	887
Viscosity at 40°C	mm ² /s	ASTM D445	101
Viscosity at 100°C	mm ² /s	ASTM D445	14
Viscosity Index	-	ASTM D2270	141
T.B.N	mgKOH/g	ASTM D2896	8.5
Pour Point	°C	ASTM D97	-33

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.