



A brand of **TOTAL**

PERFORMANCE VICTORY SC 15W-40



Mineral lubricant for diesel engines, suitable for use in on-road heavy-duty applications.

APPLICATIONS

- ELF PERFORMANCE VICTORY SC 15W-40 is a **mineral** lubricant adapted to **heavy-duty on-road diesel** engines.
- ELF PERFORMANCE VICTORY SC 15W-40 has been particularly formulated for **Euro 5 Scania** engines, and previous generations with **appropriate oil drain intervals**.

APPROVALS

Specifications	API CH-4	ACEA E5
Manufacturers' approval	Scania LDF	

PERFORMANCES AND CUSTOMER BENEFITS

- **Detergent, antioxidant and anti-corrosion properties**, allow **long oil drain intervals** that correspond to **Scania's LDF** performance level.
- **Detergent, dispersant and anti-wear additives** keep the **engine's most sensitive parts clean** and enable effective control of soot, sludge and piston deposits.

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELF PERFORMANCE VICTORY SC 15W-40		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	883
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	103.7
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.2
Viscosity Index	-	ASTM D2270	140
Flash point	°C	ASTM D92	222
Pour Point	°C	ASTM D97	-24
T.B.N	mgKOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.24

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.