

ELF SPORTI 5 15W-40 is a modern multigrade oil, using a number of carefully selected additives.

Technical Data Sheet

International
Specifications

API CF, SL

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

ELF SPORTI 5 15W-40 is particularly recommended for all Gasoline engines in modern, efficient cars and light vans, turbo-charged or naturally aspirated.

Also recommended for use in turbo-charged or naturally aspirated Diesel engines in cars and light vans.

Can be used at all temperatures for any type of driving whether in town or on the motorway.

2 - Customer Benefits

Good detergent-dispersant properties to keep engine parts clean. It particularly prevents the formation of black sludge and prevents the build-up of particles.

Good thermal stability and good oxidation resistance, preventing any premature degradation at high temperature detergent properties giving greater engine cleanliness for better performance.

Good anti-wear properties, especially in the timing system. It also has anti-corrosion and anti-foaming capability.

Shear stability ensures perfect lubrication in both hot and cold conditions. It is effective in engines burning lead-free fuel and completely harmless to catalytic converters.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	884
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	103,2
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	13,8
Viscosity index	ASTM D2270	-	136
Pour point	ASTM D97	°C	-27
Flash point	ASTM D92	°C	230
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.