SPORTI 9 A5B5 5W-30

ELF SPORTI 9 A5/B5 5W-30 is a high performance lubricant using ELF Advanced Synthetic Technology, « Fuel Economy », intended for Gasoline and Diesel car engines without post treatment system (GPF/DPF).

Technical Data Sheet

International Specifications	ACEA A5/B5 API SL
Manufacturers Approvals	Meets the requirement of : FORD WSS-M2C-913-D

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

ELF SPORTI 9 A5/B5 5W-30 is recommended for Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines without post treatment system– with or without turbocharging – in cars and light vans.

Particularly recommended to meet the enhanced requirements of direct injection Diesel engines.

Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions, for all driving styles, particularly "vigorous" and high speeds.

2 - Customer Benefits

Saves fuel and has outstanding engine protection particularly against wear.

Outstanding thermal stability and oxidation resistance, preventing any degradation even in very severe conditions.

Specially engineered to comply with car manufacturers requirements in terms of extended oil charge intervals.

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m^3	855
Kinematic Viscosity at 40°C	ASTM D445	mm^2/s	55,9
Kinematic Viscosity at 100°C	ASTM D445	mm^2/s	9,8
Viscosity index	ASTM D2270	-	169
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	230
TBN	ASTM D2896	mgKOH/g	10
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at https://ms-sds.totalenergies.com.

This product should not be used for any purposes other than the ones for which it is intended.

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.