

A multigrade oil, using a number of additives of carefully selected performance and quantity.

1 Applications

Gasoline and Diesel

- Particularly recommended for all Gasoline engines in modern, efficient cars and light vans, turbo-charged or naturally aspirated.
- Can also be used in turbo-charged or naturally aspirated Diesel engines in cars and light vans.
- Can be used at all temperatures for any type of driving whether in town or on the motorway.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

2 Performances

International Specifications

ACEA : A3/B3
API : SL/CF

3 Customer Benefits

Detergent capability

- Good detergent-dispersant properties to keep engine parts clean and in particular prevent black sludge formation and the build-up of particles.

Thermal stability

- Good thermal stability and good oxidation resistance, preventing any premature degradation at high temperature.

Anti-wear

- Good anti-wear properties, especially in the timing system.
- Anti-corrosion and anti-foaming capability.

All temperatures

- Shear stability ensuring perfect lubrication in both hot and cold conditions.
- Effective in engines burning lead-free fuel and completely harmless to catalytic converters.

4 Characteristics

	METHOD	UNITS	SAE GRADE 20W-50
Density at 15°C	ASTM D1298	kg/m ³	884
Viscosity at 40°C	ASTM D445	mm ² /s	152
Viscosity at 100°C	ASTM 445	mm ² /s	16,8
Viscosity index	ASTM D2270	-	136
Pour point	ASTM D97	°C	-27
Flash point	ASTM D92	°C	230

The typical characteristics mentioned represent mean values