TRANSELF TYPE B 75W-80

TRANSELF TYPE B 75W-80 is recommended for the lubrication of gearboxes and axles of passenger cars and vansunder very severe conditions.

Technical Data Sheet

International Specifications	API: API GL-4, API GL-4+
Manufacturers Approvals	Meets the requirements of : PSA B71 2330

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

TRANSELF TYPE B 75W-80 is recommended for the lubrication of gearboxes and axles of passenger cars and vans under very severe conditions.

TRANSELF TYPE B 75W-80 is particularly suitable when easier gear shifting is required at low temperature while maintaining optimum efficiency of the gearbox at high temperature.

2 - Customer Benefits

Gear oil with extreme-pressure and antiwear properties that allow gears to operate under tough conditions.

High resistance to deterioration at high temperatures, as well as antirust and anticorrosion protection.

Provides optimal lubrication in all temperatures, aiding in smooth gear shifting in cold weather and high-speed driving.

Ensures with its high shear stability consistent performance over time

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m^3	887
Kinematic Viscosity at 40°C	ASTM D445	mm^2/s	49
Kinematic Viscosity at 100°C	ASTM D445	mm^2/s	8
Viscosity index	ASTM D2270	-	137
Pour point	ASTM D97	°C	-45
Flash point	ASTM D92	°C	208

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at https://ms-sds.totalenergies.com.

This product should not be used for any purposes other than the ones for which it is intended.

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.