GRAISSE N 3373



Grease

Multipurpose EP grease for hub wheel bearings without heavy metals.

APPLICATIONS

Top-tier quality grease for hub wheel bearings.

- **GRAISSE N 3373** is a lithium grease with high performances. Designed for industrial and automotive applications under severe operating conditions (water, high loads, high temperatures, dust,…).
- **GRAISSE N 3373** is also suitable when a multipurpose EP grease is required in Public Works, agriculture due to its excellent mechanical stability which ensures a high bearing lifetime.

Recommendation

- Do not pollute the grease during application with dust or any other pollutants. Use preferably a pneumatic grease pump or cartridges.

SPECIFICATIONS

- ISO 6743-9: L-XDCHB2
- DIN 51 502: KP2K -40
- PSA STL S71 3103

ADVANTAGES

Multipurpose grease for high loaded applications

- Very good mechanical stability which ensures a good protection of bearings against vibrations and shocks.
- Wide temperature of use from - 40 to + 130°C.

Very good antirust protection for bearings

- Excellent adhesiveness on metallic surfaces
- Very good antiwear performances.
- Specific additivation against oxidation and corrosion.

No harmful substances (heavy metals)

- **GRAISSE N 3373** does not contain lead or any other heavy metal considered to be harmful for human health or the environment.

TYPICAL CHARACTERISTICS	METHODS	UNITS	GRAISSE N 3373
Thickener		-	lithium
NLGI Grade	ASTM D 217/DIN 51 818	-	1 ½
Color	Visuelle	-	Brown
Appearance	Visuelle		Smmoth, tacky
Temperature range		°C	- 40 to +130
Penetration at 25 °C	ASTM D 217/DIN51 818	1/10 mm	280-310
4 ball wear	ASTM D 2266	mm	< 0.6
SKF-EMCOR antirust performance with distilled water.	DIN 51 802/IP220/NFT 60-135/ISO 11007	Quotation	Max 1
Dropping Point	IP 396/NFT 60 102 C	°C	> 180
Penetration at -40°C	D 55 1133	1/10 mm	95

Above characteristics are mean values given as an information

Ce lubrifiant utilisé selon nos recommandations et pour l'application pour laquelle il est prévu ne présente pas de risque particulier.
Une fiche de données de sécurité conforme à la législation en vigueur dans la C.E. est disponible sur www.quick-fds.com et auprès de votre conseiller commercial.