



MERKAN N 4128 / SPECIS SPRAY

DESCRIPTION

Grease for vehicle body accessories.

APPLICATIONS

Non-staining grease for vehicle body accessories and machine tools, e.g. door hinges, locks, linkages, etc.

Available in aerosols.

Temperature range of use of - 40°C to 80°C.

SPECIFICATIONS

ISO - L - XDAA 1

DIN 51502 M1E - 40

Approved by Stellantis

ADVANTAGES

Good mechanical stability.

Performs well in the presence of water.

Non staining for paints.

Excellent low temperature characteristics.

Very good anti-corrosion properties.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.

TotalEnergies Lubricants

SA 552 006 454 RCS Nanterre - France

TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	MERKAN N4128 / SPECIS SPRAY
Colour	Visual	-	Beige
Texture	Visual	-	Smooth, slightly fibrous
NLGI Classification	NLGI	Grade	1
Worked penetration 60 strokes	ISO 2137	1/10 mm	305-345
Penetration at -30°C	ISO 2137	1/10 mm	170
Soap type	-	-	Calcium
Viscosity at base of oil 40°C	ASTM D445	mm ² /s	800
Dropping point	IP 396	°C	140
Antirust Performances: EMCOR	ISO 11007	rating	0 – 0
Operating temperature range		°C	- 40 to 80

Above characteristics are mean values given as an information.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.

TotalEnergies Lubricants

SA 552 006 454 RCS Nanterre - France