

Motor Oil SF 15W-40

Monograde oil for Gasoline and Diesel engines.

KEY DATA



LIGHT VEHICLE RANGE

INTERNATIONAL STANDARDS

🔥 API SF/CD

APPLICATIONS

Every condition of use (street, road, highways).

CUSTOMERS BENEFITS

- 🔥 Adapted levels of detergency and dispersancy.
- 🔥 Good Viscosity Index ensures Engine protection.
- 🔥 Modern additive technology. Good anti-wear, anticorrosion, antirust and anti-oxidation properties.

CHARACTERISTICS²

TEST	UNIT	RESULT
Viscosity grade	-	15W-40
Kinematic viscosity at 40°C	mm ² /s	107
Kinematic viscosity at 100°C	mm ² /s	14.5
Density at 15°C	kg/m ³	880
Viscosity index	-	137
Pour point	°C	-33
OC Flash point	°C	234

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

