

Quartz Ineo DID 5W-30

Engine oil

KEY DATA



LIGHT VEHICLE RANGE

GASOLINE & DIESEL ENGINE OIL
SAE 5W-30
SYNTHETIC TECHNOLOGY

INTERNATIONAL STANDARDS

- ACEA C3
- AP SN / CF

MANUFACTURER APPROVALS ¹

- VW 505.00/505.01
- MB-Approval 229.52
- Meets the requirements of GM Dexos 2
- Meets the requirements of Opel/Vauxhall OV 040 1547 - D30

¹ Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. It's unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

Quartz Ineo DID 5W-30 is suitable for vehicles equipped with a pump injection system.

This 5W-30 grade lubricant is suitable for the harshest conditions of use (sports driving, repeated start-ups, city and motorway driving).

Quartz Ineo DID 5W-30 meets the needs of GASOLINE and Diesel motors and particularly motors equipped with pump injectors.

CUSTOMERS BENEFITS

- 💧 Engine Protection: Quartz Ineo DID 5W-30 ensures the protection and durability of engine parts.
- 💧 Engine Cleanliness: This oil ensures good engine cleanliness.
- 💧 Quartz Ineo DID 5W-30 is particularly suitable for engines produced by the Volkswagen group (Volkswagen, Audi, Seat, Skoda).

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	5W-30
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	69.3
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	11.9
Density at 15°C	kg/m ³	ASTM D1298	852
Viscosity index	-	ASTM D2270	169
Pour point	°C	ASTM D97	-36
OC Flash point	°C	ASTM D92	230

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubricants / Last update of this datasheet: July 22 / Quartz Ineo DID 5W-30

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.