

Tractagri HDM 15W-40

Engine oil

KEY DATA



Mineral lubricant for turbocharged engines used in Agricultural machinery.

INTERNATIONAL STANDARDS

- 🔥 API CF-4/SG

MEETS THE REQUIREMENTS OF

- 🔥 MAN 271
- 🔥 MB 228.1
- 🔥 Deutz DQC I-02

SUITABLE FOR

- 🔥 CASE, NEW-HOLLAND, CLAAS, FENDT, SAME,
- 🔥 MASSEY FERGUSON, Mc CORMICK, VALTRA...

APPLICATIONS

Tractagri HDM 15W-40 is recommended for agricultural Diesel engines, especially technologies without pollution control.

This lubricant is adapted to naturally-aspirated or turbocharged Diesel engines, and also service vehicle gasoline engines.

Tractagri HDM 15W-40 is suitable for every tractors or agricultural equipments used in soft conditions.

PERFORMANCES & CUSTOMERS BENEFITS

- 🔥 Tractagri HDM 15W-40 contains viscosity stability in service.
- 🔥 This lubricant exhibits thermal stability and oxidation resistance, ensuring proper engine lubrication.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	888
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	110
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	13.8
Viscosity index	-	ASTM D2270	125
Pour point	°C	ASTM D97	-27
T.B.N	mgKOH/g	ASTM D2896	12

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

